


Prime11 XT

Standard & High Capacity


Extra Tough Pleated Air Filters

FEATURES

- MERV 11 efficiency
- Low pressure drop
- High dust holding capacity
- Extended surface
- Heavy duty wire support
- Heavy duty moisture resistant frame
- Available in 1, 2, & 4" depths
- Max operating temp: 180°F



Prime11 XT is up for the demands of the toughest applications



The unique design of the Prime11 XT delivers maximum performance at a low energy consumption

PRIME11 XT & PRIME11HC XT CONSTRUCTION & APPLICATIONS


The Prime11 XT filter is designed for the toughest industrial applications, featuring a robust die-cut frame and heavy-duty wire backing that ensure superior durability. It is available in both standard and high-capacity versions (Prime11HC XT) and comes in 1", 2", and 4" depths to meet diverse filtration needs.

Extensive testing confirms the Prime11 XT's impressive service life and high dust-holding capacity (DHC). Its specially engineered fibers increase surface area, enhancing particulate capture efficiency compared to standard filter media.


The heavy-duty galvanized steel backing adds structural strength, making the filter 40% more rigid than conventional pleated filters. It can handle pressure drops up to 7 in. w.g. with minimal deflection, ensuring reliable performance and low resistance. Rated MERV 11, the Prime11 XT provides exceptional dust-holding capacity and a long service life, making it a top choice for demanding industrial environments.

TECHNICAL DATA

PRIME11 XT & PRIME11HC XT



PRIME11 XT & PRIME11HC XT



PRIME11 XT & PRIME11 HC XT
PERFORMANCE DATA

Nominal Depth	Nominal Size (in.) (WxHxD)	Actual Size (in.)			Air Flow @ Capacity (CFM)	Resistance @ Capacity (in. w.g.)		Total Media Area (sq. ft.)	Number of Pleats Per Linear Foot							
		Width	Height	Depth		STD	HIGH		STD	HIGH						
1"	10x20x1	9.50	19.50	0.75	417	0.28	0.23	2.5	13	15						
	12x20x1	11.50	19.50		500			3.1								
	12x24x1	11.50	23.50		600			3.7								
	14x25x1	13.50	24.50		729			4.5								
	15x20x1	14.50	19.50		625			3.9								
	15x25x1	14.50	24.50		781			4.9								
	16x20x1	15.50	19.50		667			4.2								
	16x24x1	15.50	23.50		800			5.0								
	16x25x1	15.50	24.50		833			5.2								
	18x20x1	17.50	19.50		750			4.7								
	18x24x1	17.50	23.50		900			5.7								
	18x25x1	17.50	24.50		938			5.9								
	20x20x1	19.50	19.50		833			5.2								
	20x23x1	19.50	22.50		958			5.7								
	20x24x1	19.50	23.50		1000			6.3								
	20x25x1	19.50	24.50		1042			6.6								
	20x30x1	19.75	29.75		1250			6.9								
	24x24x1	23.50	23.50		1200			7.6								
	24x30x1	23.875	29.875		1500			8.3								
	24x36x1	23.75	35.75		1800			10.0								
	25x25x1	24.50	24.50		1302			7.2								
	2"	10x20x2	9.50		19.50			1.75			700	0.25	0.22	6.0	10	15
		12x20x2	11.50		19.50						833			4.8		
		12x24x2*	11.38		23.38						1000			8.7		
		14x20x2	13.50		19.50						975			8.5		
14x25x2		13.50	24.50	1220	10.7											
15x20x2		14.50	19.50	1040	9.1											
16x20x2*		15.50	19.50	1110	9.8											
16x24x2*		15.38	23.38	1333	11.8											
16x25x2*		15.50	24.50	1390	12.2											
18x20x2		17.50	19.50	1250	11.0											
18x24x2*		17.38	23.38	1500	13.3											
18x25x2		17.50	24.50	1565	13.8											
20x20x2*		19.50	19.50	1390	12.3											
20x24x2*		19.38	23.38	1670	14.8											
20x25x2*		19.50	24.50	1740	15.4											
20x30x2		19.75	29.75	2083	12.5											
24x24x2*		23.38	23.38	2000	17.8											
24x30x2		23.50	29.50	2500	15.0											
25x25x2		24.50	24.50	2170	12.9											
4"		12x24x4	11.38	23.38	3.75	1000	0.21		0.15	11.2	9			12		
		16x20x4	15.50	19.50		1110				12.6						
		16x24x4	15.50	23.50		1333				15.2						
		16x25x4	15.50	24.50		1390				15.8						
		18x24x4	17.38	23.38		1500				17.1						
		20x20x4	19.50	19.50		1390				15.8						
	20x24x4	19.38	23.38	1670		19.0										
	20x25x4	19.50	24.50	1740		19.8										
	24x24x4	23.38	23.38	2000		23.0										
	25x29x4	24.50	28.50	2517		29.0										

- Notes:
- * These sizes utilize the new 28pt die-cut frame, currently all other sizes utilize the standard prime die-cut frame
 - Recommended final resistance = 1.50 in. w.g.
 - 1 in. depth is rated at 300 FPM
 - 2 & 4 in. depths are rated at 500 FPM
 - Performance data is based on ASHRAE Test Standards 52.2
 - Max operating temp: 180°F

MANN+HUMMEL is committed to continual product development – all descriptions, specifications and performance data are subject to change without notice. MANN+HUMMEL products are manufactured to exacting criteria – there can be a ±5% variance in filter performance.

LOCAL REPRESENTATIVE

