


Nanoclass Square Pro Membrane KE

Product Range



Features



Applications



Filter Class



KEY FACTS

- High efficiency (H14 > 99.995 % at MPPS)
- Integral knife-edge for use with gel-seal grid ceiling systems
- Available in depth of 109 mm
- High tensile strength
- 100% boron free
- Minipleat technology for laminar flow
- Extremely low pressure drop
- Guaranteed leak free

DESIGN

e-PTFE membrane filter media folded into a pack and sealed into an anodized aluminum frame with integrated knife-edge.

APPLICATIONS

Final filter for clean rooms and clean workbenches that use gel-seal grid systems. For separation of viruses, bacteria, toxic dust and aerosols, in hospitals/medical institutes, chemists, laboratories, clean rooms, pharmacy, food processing industry, microelectronics.

Nanoclass Square Pro Membrane KE

PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop	Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	EN 1822	mm	m³/h	Pa		EN 1822	mm	m³/h	Pa
800522024205	H14	305 x 305 x 109	150	55	800522024212	H14	610 x 762 x 109	750	55
800522024206	H14	305 x 610 x 109	300	55	800522024213	H14	610 x 915 x 109	900	55
800522024207	H14	305 x 762 x 109	375	55	800522024215	H14	610 x 1220 x 109	1200	55
800522024208	H14	305 x 915 x 109	450	55	800522024214	H14	762 x 915 x 109	1130	55
800522024209	H14	457 x 457 x 109	350	55	800522024216	H14	762 x 1220 x 109	1500	55
800522024210	H14	457 x 610 x 109	450	55	800522024217	H14	1220 x 1220 x 109	2400	55
800522024211	H14	610 x 610 x 109	600	55	800522024217	H14	1220 x 1220 x 109	2400	55

SPECIFICATION

Recommended air flow	Flow rate \pm 10 %	Recommended final pressure drop	450 Pa (max. 600 Pa)
Heat resistance	Up to 70 °C (Peak 90 °C)	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	No

OPTIONS

Gasket	Continuous polyurethane foam or flat neoprene
Grid	1 or 2 sides