

Airpocket Eco

Long-life bag filter

Product Range



Applications



Filter Class

G

Coarse



KEY FACTS

- Long service life
- Fully incinerable
- Free of glass fibers
- Low pressure drop

DESIGN

Progressively-structured synthetic media in a polypropylene frame.

APPLICATIONS

Prefiltration or main filtration for air-conditioning and ventilation systems.

Airpocket Eco

Long-life bag filter

PERFORMANCE DATA

Filter Class		Dimensions	Pockets	Flow Rate	Pressure Drop
ISO 16890	EN 779	mm		m ³ /h	Pa
Coarse 70%	G4	287 x 592 x 360	2	1700	45
Coarse 70%	G4	592 x 592 x 360	4	3400	45
Coarse 70%	G4	287 x 592 x 500	2	1700	40
Coarse 70%	G4	592 x 592 x 500	4	3400	40
Coarse 70%	G4	287 x 592 x 635	2	1700	35
Coarse 70%	G4	592 x 592 x 635	4	3400	35

SPECIFICATION

Recommended air flow	Flow rate \pm 15 %	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes (excluding metal frame versions)

OPTIONS

Frame	Galvanized steel or plastic
Header depth	25 mm