

Airroll Select

Glass Automatic RFF

Product Range



Features



Applications



Filter Class

G

Coarse



KEY FACTS

- Compatible with Farr and Schirp automatic roll filter hardware
- High dust holding capacity
- Wound for standard or reverse flow
- Odor free

DESIGN

Continuously-spun glass fiber media, tension wound onto a cardboard tube.

APPLICATIONS

Replacement filter roll for installation in Farr and Schirp systems.

Airroll Select

Glass Automatic RFF

PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Pressure Drop
	ISO 16890	EN 779	mm	Pa
800122027894	Coarse 70%	G3	838 x 20000 x 60	48
800122027895	Coarse 70%	G3	1143 x 20000 x 60	48
800122027896	Coarse 70%	G3	1448 x 20000 x 60	48
800122027897	Coarse 70%	G3	1753 x 20000 x 60	48
800122027898	Coarse 70%	G3	2056 x 20000 x 60	48

SPECIFICATION

Recommended air velocity	2.5 m/s	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 65 °C	Moisture resistance	80 %
Regenerable	No	Incinerable	No