

# Airroll Select Glass Automatic RFM

---

## Product Range



---

## Features



---

## Applications



---

## Filter Class

G

Coarse



## KEY FACTS

- Compatible with CEAG and AAF roll filter systems
- High dust holding capacity
- Wound for standard or reverse flow
- Odor free

## DESIGN

Continuously-spun glass fiber media, tension wound onto a steel spool with end plates.

## APPLICATIONS

Replacement filter roll for installation in CEAG and AAF systems.

# Airroll Select Glass Automatic RFM

## PERFORMANCE DATA

| Article No.  | ISO 16890  | Filter Class | Dimensions        | Pressure Drop |
|--------------|------------|--------------|-------------------|---------------|
|              |            | EN 779       | mm                | Pa            |
| 800122027877 | Coarse 70% | G3           | 526 x 20000 x 60  | 48            |
| 800122027878 | Coarse 70% | G3           | 836 x 20000 x 60  | 48            |
| 800122027879 | Coarse 70% | G3           | 1141 x 20000 x 60 | 48            |
| 800122027880 | Coarse 70% | G3           | 1446 x 20000 x 60 | 48            |
| 800122027881 | Coarse 70% | G3           | 1751 x 20000 x 60 | 48            |
| 800122027893 | Coarse 70% | G3           | 2056 x 20000 x 60 | 48            |

## SPECIFICATION

|                                 |             |  |   |
|---------------------------------|-------------|--|---|
| <b>Recommended air velocity</b> | 2.5 m/s     | <b>Rec. final pressure for efficient energy use acc. to EN 13053</b> | Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3 |
| <b>Heat resistance</b>          | Max. 120 °C | <b>Moisture resistance</b>   | 80 %  |
| <b>Regenerable</b>              | No          | <b>Incinerable</b>   | No  |