

# Aircube Pro Refill

## Product Range



## Features



## Applications



## Filter Class

M

F

ePM10

ePM2.5

ePM1



## KEY FACTS

- Changeable filter system
- Simple filter-change process requiring no tools
- Lightweight for easy installation
- Incinerable
- Metal and silicon free
- Reduces waste and disposal costs

## DESIGN

Replaceable filter cells made from microglass paper media with thermoplastic separators. Cells are held in place with a tongue and groove profile and sealed with a rubber gasket.

## APPLICATIONS

Prefiltration or main filtration for all HVAC systems.



# Aircube Pro

## Refill

### PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Flow Rate*	Pressure Drop	Energy Consumption	Energy Class
	ISO 16890	EN 779					
800455000028	ePM10 75%	M6	360 x 550 x 53	3400	90	1144	D
800455000019	ePM2.5 55%	F7	360 x 550 x 53	3400	90	1121	C
800455000023	ePM1 80%	F9	360 x 550 x 53	3400	115	1529	C

\* Flow rate based on two Vs installed in a 592 x 592 mm holding frame

### SPECIFICATION

<b>Recommended air flow</b>	Flow rate $\pm$ 20 %	<b>Rec. final pressure for efficient energy use acc. to EN 13053</b>	Lowest value of initial pressure drop + 100 Pa, or initial pressure drop x 3
<b>Heat resistance</b>	Max. 80 °C	<b>Moisture resistance</b>	100 % rel. humidity
<b>Regenerable</b>	Yes	<b>Incinerable</b>	Yes