


# Airsquare Select Power

## Product Range



Select

## Features



## Applications



## Filter Class

M

Coarse



## KEY FACTS

- Large filter area with space-saving, shallow depth
- Stable compact design
- Low weight
- High efficiency
- Easy assembly and handling

## DESIGN

Mini-pleated synthetic media with a robust plastic frame.

## APPLICATIONS

Prefiltration for gas turbine air intakes.

# Airsquare Select Power

## PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Flow Rate	Pressure Drop
	ISO 16890	EN 779	mm	m <sup>3</sup> /h	Pa
800234029917	Coarse 70%	M5	592 x 592 x 48	3400	90
800234000617	Coarse 70%	M5	592 x 592 x 96	3400	50

## SPECIFICATION

<b>Recommended air flow</b>	Flow rate $\pm$ 25 %	<b>Recommended final pressure drop</b>	250 Pa (max. 450 Pa)
<b>Heat resistance</b>	Max. 80 °C	<b>Moisture resistance</b>	100 % rel. humidity
<b>Regenerable</b>	No	<b>Incinerable</b>	Yes

## OPTIONS

<b>Frame</b>	Plastic, galvanized steel or stainless steel
<b>Gasket</b>	Foamed polyurethane continuous gasket, 1 or 2 sides