

# Airroll Select

## Glass Automatic RFD

---

### Product Range



Select

---

### Features



---

### Applications



---

### Filter Class

G

Coarse



### KEY FACTS

- Compatible with Delbag automatic roll filter hardware
- High dust holding capacity
- Wound for standard or reverse flow
- Odor free

### DESIGN

Continuously-spun glass fiber media, tension wound onto a cardboard tube.

### APPLICATIONS

Replacement filter roll for installation in Delbag systems.

# Airroll Select

## Glass Automatic RFD

### PERFORMANCE DATA

Article No.		Filter Class	Dimensions	Pressure Drop
	ISO 16890	EN 779	mm	Pa
800122027888	Coarse 70%	G3	810 x 20000 x 60	48
800122027889	Coarse 70%	G3	1110 x 20000 x 60	48
800122027890	Coarse 70%	G3	1410 x 20000 x 60	48
800122027891	Coarse 70%	G3	1710 x 20000 x 60	48
800122027892	Coarse 70%	G3	2010 x 20000 x 60	48

### SPECIFICATION

<b>Recommended air velocity</b>	2.5 m/s	<b>Rec. final pressure for efficient energy use acc. to EN 13053</b>	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
<b>Heat resistance</b>	Max. 80 °C	<b>Moisture resistance</b>	80 %
<b>Regenerable</b>	No	<b>Incinerable</b>	No