

Airroll Select

Glass Automatic RFT

Product Range



Features



Applications



Filter Class

G

Coarse



KEY FACTS

- Compatible with Trox automatic roll filter hardware
- High dust holding capacity
- Wound for standard or reverse flow
- Odor free

DESIGN

Continuously-spun glass fiber media, tension wound onto a cardboard cassette with a metal shaft.

APPLICATIONS

Replacement filter roll for installation in Trox systems.

Airroll Select

Glass Automatic RFT

PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Pressure Drop
	ISO 16890	EN 779	mm	Pa
800122027882	Coarse 70%	G3	650 x 20000 x 60	48
800122027883	Coarse 70%	G3	950 x 20000 x 60	48
800122027884	Coarse 70%	G3	1250 x 20000 x 60	48
800122027885	Coarse 70%	G3	1550 x 20000 x 60	48
800122027886	Coarse 70%	G3	1850 x 20000 x 60	48
800122027887	Coarse 70%	G3	2150 x 20000 x 60	48

SPECIFICATION

Recommended air velocity	2.5 m/s	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 120 °C	Moisture resistance	80 %
Regenerable	No	Incinerable	No