

Carboactiv Tube

Activated carbon cylinder

Product Range



Features



Applications



KEY FACTS

- Extremely high capacity
- Odor-neutralizing
- Refillable (metal version only)
- Low pressure drop

DESIGN

Galvanized steel, stainless steel and plastic cartridges, which can be filled with a wide variety of activated carbon and mediums.

APPLICATIONS

Suitable for air-conditioning systems and range of industrial processes. Also available for the removal of radioactive and hazardous gases.

Carboactiv Tube

Activated carbon cylinder

PERFORMANCE DATA

Article No.	Dimensions	Flow Rate	Filling Level	Unit
	mm	m ³ /h	Kg	
AC.C.250	ø = 145 mm, l = 250 mm	250	1	8 pcs. / box
AC.C.450	ø = 145 mm, l = 450 mm	300	2	4 pcs. / box
AC.C.600	ø = 145 mm, l = 600 mm	350	3	4 pcs. / box

MOUNTING FRAMES

Article No.	Designation	Dimensions	Unit
		mm	
AC.F.16	Mounting frame for 16 cartridges	610 × 610 × 100 mm	Piece
AC.F.12	Mounting frame for 12 cartridges	508 × 610 × 100 mm	Piece
AC.F.08	Mounting frame for 8 cartridges	305 × 610 × 100 mm	Piece
AC.F.04	Mounting frame for 4 cartridges	305 × 305 × 100 mm	Piece

SPECIFICATION

Heat resistance	0 °C – 40 °C	Moisture resistance	Up to 70 % rel. humidity
Fill material	Pellet carbon 3 mm coconut shell	Layer thickness	26 mm