

Airpocket Eco

Long-life bag filter

Product Range



Applications



Filter Class

G

Coarse



KEY FACTS

- Long service life
- Fully incinerable
- Free of glass fibers
- Low pressure drop

DESIGN

Progressively-structured synthetic media in a polypropylene frame.

APPLICATIONS

Prefiltration or main filtration for air-conditioning and ventilation systems.

Airpocket Eco

Long-life bag filter

PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Pockets	Flow Rate	Pressure Drop
	EN 779	ISO 16890	mm		m ³ /h	Pa
800355012908	G4	Coarse 70%	287 x 592 x 360	2	1700	45
800355012906	G4	Coarse 70%	592 x 592 x 360	4	3400	45
800355013001	G4	Coarse 70%	287 x 592 x 500	2	1700	40
800355012993	G4	Coarse 70%	592 x 592 x 500	4	3400	40
800355012822	G4	Coarse 70%	287 x 592 x 635	2	1700	35
800355012784	G4	Coarse 70%	592 x 592 x 635	4	3400	35

SPECIFICATION

Recommended air flow	Flow rate \pm 15 %	Recommended final pressure drop	2 to 2.5 times initial pressure drop
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes (excluding metal frame versions)

OPTIONS

Frame	Galvanized steel or plastic
Header depth	25 mm